

Supported by the PAXSTORE open software distribution platform, within which payment service providers create and manage their own independent appstore marketplaces.

The A930 is a new generation PCI PTS 5.x and NFC contactless certified smart mobile terminal with a state of the art processor and Android 7.1. With inbuilt 4G, WiFi and Bluetooth connectivity and a high capacity battery, the A930 keeps you always connected, ensuring

peak performance during business hours.

The A930 fits comfortably in the hand and the stunning high definition 5.5-inch touchscreen display offers a graphical user interface way superior to traditional POS terminals. The A930 has inbuilt dual cameras with LED flashlight which can read 1D and 2D codes. An optional base caters to all types of merchant environments.





## **FEATURES & BENEFITS**

## **Unprecedented Security**

- Ultra-safe security processor
- USBType-C charging port
- Supports RSA, AES, 3DES
- PCT PTS 5.x Certified
- NFC contactless

## **Exceptional Performance**

- Dual cameras for 1D / 2D code scanning
- 4G / Bluetooth / WiFi connectivity
- Micro SD expandability
- Large 5.5-inch display



A930
Android Mobile
Terminal

## **SPECIFICATIONS**

OS	PayDroid Powered by Android 7.1
Processor	Application CPU: Quad-core Cortex-A53, 1.4GHZ Security CPU: 32-bit RISC Core (ARMv7-M), 1.25DMIPS/MHz
Memory	1GB DDR + 8GB eMMC   2GB DDR + 16GB eMMC (optional) 1 x Micro SD Card Slot, Supports up to 128GB
Card Readers	Magnetic Card Reader   Smart Card Reader   Contactless Card Reader
Cameras	0.3 Megapixel Fixed Focal Front Camera   5 Megapixel Auto Focus Rear Camera with LED Flashlight   Reads 1D & 2D Codes
Display	5.5-inch IPS Display   HD 1280 x 720 pixels   CapacitiveTouchscreen
Audio	1 x Speaker Volume up to 85 dB   1 x Microphone
Physical Button	1 x ON/OFF Button   2 x Volume +/- Button
Communications	WIFI 2.4G, 5G (optional) Supports Hotspot   4G (TD-LTE / FDD-LTE) + 3G (WCDMA / CDMA2000) + 2G (GSM / GPRS)   Bluetooth (4.2)
Card Slots	1 x SIM + 2 x SAM   2 x SIM + 1 x SAM (optional)
Peripheral Ports	1 x Type C Supports charging and USB 2.0, OTG   1 x 3.5mm Audio Jack 6pin POGO pin
Printer	2-inch Thermal Printer   Print Speed: 80mm/s   PaperWidth: 58mm PaperDiameter: 40mm
Battery	7.2V / 2600mAh Rechargeable Li-ion Battery
Adapter	Input: 100 - 240V AC, 50Hz / 60Hz   Output: 5.0V DC, 2.0A
Sensors	Light sensor   G-Sensor (optional)
Location	GPS   BeiDou   Glonass
Accessories	Charging Base (optional)   Wireless Base (optional) Multifunctional Base (optional)
Indicators	4 xContactless Transaction Lights   Charging Indicator Smart Card Reader Indicator
Physical	L x W x H (mm) : 190 x 84.4 x 65.8 Weight (g) : 470 (Including Battery)
Environmental	-10°C $\sim$ 50°C (14°F $\sim$ 122°F) Operating Temperature I -20°C $\sim$ 70°C (-4°F $\sim$ 158°F) Storage Temperature I 5% $\sim$ 95% Relative Humidity, Non-Condensing
Certifications	PCI PTS 5.x, SRED   EMV L1 & L2   EMV Contactless L1   MasterCard TQM Visa payWave   American ExpressPay   MasterCard Contactless   ABECS Discover D-PAS   Interac_Flash L2   APCA   CE   Anatel   RoHs







