

Q58

COMPACT Countertop



Food & Beverage



Fashion & Retail



Supermarkets



CLASSIC



Powered by
Nuxiums-std



PCI 6
SRED



2.8"
Color Display




















0.3MP
Front



Advanced
Connectivity

SPECIFICATIONS

	Operating System	Nuxiums-std
	Processor	Cortex A5
	Memory	128MB FLASH + 128MB DDR SDRAM 256MB FLASH + 256MB DDR SDRAM (optional)
	Card Readers	Chip & PIN Contactless Magnetic Stripe
	Cameras	Optional 0.3MP Front-Facing
	Display	2.8" 240 x 320 Color Screen
	Comms Configurations	LAN Modem (optional) WiFi 2.4GHz (optional) 4G Cat-1(optional)
	Power Supply	Input: 100-240V AC, 0.2A, 50Hz/60Hz Output: 9.0V DC, 1.0A
	Printer	40 Lines/Sec Paper Roll Outer Diameter: 40mm
	SIM / SAM	2 x SAM 1 x SIM (optional)
	Keys / Buttons	18 Keys: 0~9 Menu Func Up Down Alpha Enter Clear Cancel
	Audio	1 Buzzer
	Ports	1 RS232 1 Line 1 Ethernet 1 Type-C USB OTG 1 DC Power Jack
	Physical	186 x 79 x 70mm
	Environmental	-10°C ~ 50°C (14°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 10% ~ 93% Relative Humidity, Non-condensing
	Accessories	Privacy PIN Shield (optional)
	Certifications	PCIPTS 6.x EMV L1&L2 EMV Contactless L1 MasterCard PayPass Visa PayWave American ExpressPay Discover D-PAS Interac Flash L2 TQM CE RoHS

